Cyber Power





CSP300WUR1 Professional Surge Protector

Offering home/office environments with computer and communication grade surge protection.

The CyberPower Professional Series CSP300WUR1 Surge Protector is ideal for Home/Office protection with 600 joules, 3 outlets, 2 USB 2.1 Amp charging ports, and a convenient wall tap design. The surge protector is ideal for protecting personal computers, phones/fax/modems, printers, stereos, and other electronics. Its 2.1 Amp USB charging ports are perfect for keeping tablets, smart phones, and other rechargeable electronics ready to use.

The CSP300WUR1 features three (3) outlets, wall tap plug, MOV technology to guard the surge protector and connected electronics against line abnormalities, and lightning surges, while EMI/RFI filters block unwanted line noise.

A Limited-Lifetime Warranty ensures that this surge protector has passed our highest quality standards in design, assembly, material or workmanship and further protection is offered by a \$50,000 Connected Equipment Guarantee.

Typical Applications

- Desktop Computers
- Routers & Modems
- Personal Electronics

Features

- 3 Surge Protected Outlets
- 600 Joules of Surge Protection
- (2) USB Charging Ports 2.1 Amp
- Wall Tap Plug
- MOV Surge Protection
- 15A Circuit Breaker
- EMI/RFI Noise Filters
- \$50,000 CEG
- Lifetime Warranty

CSP300WUR1 Professional Surge ProtectorOffering home/office environments with computer and communication grade surge protection.

| GENERAL | |
|-------------------------------|----------------------------------|
| Туре | Professional Series |
| Phase | Single Phase |
| INPUT | |
| Voltage | 125V |
| Circuit Breaker | 15 Amp |
| Plug Type | 12Vdc Auto Power Port |
| Plug Style | Wall Tap |
| OUTPUT | |
| Outlets - Total | 3 |
| Outlet Type | NEMA 5-15R |
| USB Charging Ports | 2 - 5Vdc @ 2.1A |
| SURGE PROTECTION & FILTERING | |
| Surge Suppression | 600 Joules |
| Maximum Surge Current | 30,000 Amps |
| Maximum Surge Current H-N | 15,000 Amps |
| Maximum Surge Current H-G | 15,000 Amps |
| Clamping Voltage | 400V (L-N, L-G) |
| Response Time | < 1 nanosecond |
| EMI/RFI Filtration | 150KHz to 100MHz |
| Attenuation | Up to 32dB |
| EMI/RFI Filtration | 150KHz to 100MHz |
| Attenuation | Up to 70dB |
| INDICATORS | |
| Indicators | Protected (Green) |
| PHYSICAL | |
| Form Factor | Wall Tap |
| Enclosure Construction | ABS |
| Color | Black |
| CERTIFICATIONS | |
| Safety | UL1363 / UL1449 3rd Edition, cUL |
| Environmental | RoHS Compliant |
| WARRANTY | |
| Product Warranty | Limited Lifetime |
| Connected Equipment Guarantee | Lifetime |
| CEG Amount | \$50,000 |